

Fleximax L35		<div> <div>NBR Nitrile</div> <div>Immersion</div> </div>	
COATING MATERIAL	Nitrile	<b>DESCRIPTION</b> <ul style="list-style-type: none"> <li>▪ Excellent resistance to abrasion and small cuts.</li> <li>▪ Chemical resistance to solvents, acids, bases, oils, greases, petrol and alcohol.</li> <li>▪ This protective glove has a remarkable grip in dry environment.</li> <li>▪ AQL 1.5</li> </ul>	<div> <div> <div>EN 388 4121</div> <div>EN 374 JKL</div> <div>EN 374</div> </div> <div>CATEGORY III</div> </div>
LINER MATERIAL	Interlock cotton		
CUFF STYLE	Gauntlet		
THICKNESS MM	0.90		
COLOUR	Green		
EN SIZE	8, 9, 10, 11		
LENGTH MM	350		
PACKAGING	12 pairs in a bag; 8 bags in a carton		

High flexibility and excellent dexterity

PRIMARY INDUSTRIES



IDEAL APPLICATIONS

- Agrochemicals
  - Chemical processing and preparation
  - Defence industry
  - Degreasing
  - Handling acids, caustics and solvents
- Maintenance
  - Metal fabrication
  - Petrochemicals
  - Public utilities
  - Refining - Oil & Petrol
  - Sub-assembly handling
  - Tank filling



Fleximax L35